
### **PVE3250 Series**


### **Propylene Valves for DOT Cylinders**






PVE3250R-435





PVE3250CLG435





Designed for applications in production welding and cutting and supplying of fuel gases.

#### **Key Features & Benefits**

- · Internal pressure relief valve
- · Designed for 420 lb. DOT cylinder
- Compatible with both 4BW240 and 4BW260 cylinders
- · Start to discharge pressure 435 PSI
- Compliant with CGA Technical Bulletin 27
- Rugged C36600 brass body construction
- Pressure Relief Device (CGA S-1.1 recommends replacing every 10 years)

#### **Special Features for PVE3250R**

- Compatible with both propane and propylene, 4BW240 and 4BW260 cylinders
- Includes replaceable PRV (CGA recommends replacing every 10 years)
- · Tamper-resistant bonnet

Materials of Construction for PVE3250 Valves				
Sherwood Part Number	Part Description	Materials of Construction		
N/A	Body Brass C37700			
	Bonnet & Stem Assembly			
	Bonnet	Brass C36000		
3250-8LH	Upper Stem	PTFE Coated Brass C36000		
	0-Ring	Buna-N		
	Lubricant	Drakeol #9 Oil		
	Lower Stem	Brass C36000		
	Seat	Nylon		
1901	Handwheel	Aluminum		
3740-13	Handwheel Screw	Plated Steel		
3250R-10	Safety Assembly			
	Safety Body	Brass C36000		
	Spring	Stainless Steel		
	Safety Seat Holder	Glass Filled Nylon		
	Safety Seat	Buna-N		
	Safety Retainer	Brass C36000		
N/A	Bonnet Locking Pin	Plated Hardened Steel		
3250R-19	Protective Cap	Vinyl		
N/A	Thread Sealant	Everseal 183		

For Product Markings Reference, see (F) on page 66.

## **PVE3250 Series**

# **Propylene Valves**

Ordering Information						
Sherwood Part Number	Cylinder Type	CGA Outlet Connection	Inlet Connection	Start to Discharge Setting (PSI)	Special Features	
PVE3250C-435	4B260, 4BA260, 4BW260	510	3⁄4"-14 NGT	435–520	_	
PVE3250CLG435-XX.X*	4B260, 4BA260, 4BW260	510	3⁄4"-14 NGT	435–520	Liquid Level Gauge, Dip Tube	
PVE3250R-435	4B260, 4BA260, 4BW260, 4BW240	510	3⁄4"-14 NGT	435–480	Replaceable CG-7 Pressure Relief Device	
PVE446B	4B260, 4BA260, 4BW260	1.000-20 UNEF-2B	1"-11.5 NPT	435–520	Relief Valve for Propylene Service Only	

<sup>\*</sup> XX.X — Specify length of dip tube relative to cylinder size.

Key Replacement Parts	
3250-8LH-KIT	Bonnet Assembly Kit for PVE3250C and PVE3250CLG
3250R-10-KIT	50 Replaceable Pressure Relief Devices for PVE3250R-435
TL3250R	Tool for Replaceable CG-7



TL3250R